

TFT LCD Display for Industrial application

UOF00-L170A-M1

17" Open Frame Display

RGB / DVI / Video / Touch Screen



- * Information kiosk, Banking terminal, Entertainment display
- * Video game machine, Casino game machine
- * Medical equipment, Multimedia display for advertising
- * Measuring instrument & Testing equipment system
- * Elevator information display, Fish - finder, etc.

Model No	Analog RGB + DVI	UOF00-L170A-M1 (Standard Type)
	Analog RGB + DVI + Video(S-video + Composite)	UOF00-L170C-M1 (Video Type)

Specification

Optical Spec	Panel supplier	LG.Philips / SAMSUNG
	Model Name	LM170E01-TLAX
	Resolution	SXGA 1280 x 1024
	Brightness	250 cd/m ²
	Contrast Ratio	600:1
	Viewing Angle (U/D,L/R)	75°/65° , 70°/70°
	Response Time	8 ms
	Colors	16.2M

Hardware Spec	Interface	VGA Input : D-Sub15 pin, DVI / Video Input : Composite, S-Video
	Power	Input : 100 ~ 240V , 50~60Hz / Output : DC 12V, 3.5A
	OSD Control	Auto adjust, Brightness, Contrast, Hori. / Vert. Position, Clock, phase, Color, Language..
	Mechanical &	Temperature : 0°C to 50°C Operating / -20°C to 60°C Storage
	Environmental	Humidity : 10%RH to 90%RH Operating / 10%RH to 90%RH Storage
	Power Consumption	25 Watts (Max)
	Plug & Play	DDC 1/2B
Accessories	15-PIN VGA cable, Power cord, AC adapter	

Option	Touch Screen	5 Wire Resistive Touch	3M Touch / ELO Touch / Inno Touch / Han Touch
		Capacitive Touch	3M Touch / Digitech Touch
		Saw Touch	ELO Touch / General Touch
		NFI Touch	3M Touch
		Privacy Filter	3M Touch

Dimension	Open frame dimension	375 (H) x 314 (V) x 52 (T) mm
-----------	----------------------	-------------------------------

*The specification is subject to be changed without notice.

*If you need more information of the products such as mechanical drawing, download or contact by e-mail

Address : 1392 Poinsettia Ave., Suite E, Vista, CA 92081-8507

Tel : 760-295-2917, 2918 / Fax : 760-295-2932

Web : www.utitechnology.com